

JoshRub

247 Paraffinic Rubber Process Oil

Product Description

JoshRub is a premium Premium Paraffinic Base Oil Paraffinic Rubber Process Oil designed for High performance EPDM, automotive weatherseals, high temperature applications. Meets IS 13631, ASTM D2226 Type 102 specifications and delivers exceptional performance in demanding conditions.

Technical Specifications

Appearance	Light amber liquid
Density at 15°C	0.875-0.885 g/cm³
Kinematic Viscosity at 40°C	180-220 cSt
Kinematic Viscosity at 100°C	16-19 cSt
Viscosity Index	105 min
Flash Point (COC)	270°C min
Pour Point	-3°C max
Aniline Point	120-132°C
Carbon Type Analysis - CA%	< 1%
Carbon Type Analysis - CN%	18-26%
Carbon Type Analysis - CP%	75-80%
Sulphur Content	0.02% max
Color ASTM	L 1.5 max
Volatility (Noack)	< 8%

Applications

High performance EPDM, automotive weatherseals, high temperature applications

Performance Standards

IS 13631

Handling & Storage

- Store in a cool, dry place away from direct sunlight
- Keep container tightly closed when not in use
- Shelf life: 36 months from date of manufacture
- Do not mix with other lubricants