

JoshRub

248 Paraffinic Rubber Process Oil

Product Description

JoshRub is a premium Ultra-Refined Paraffinic Base Oil Paraffinic Rubber Process Oil designed for Premium EPDM compounds, automotive door seals, window profiles, white/colored rubber. Meets IS 13631, ASTM D2226 Type 101 specifications and delivers exceptional performance in demanding conditions.

Technical Specifications

Appearance	Light amber liquid
Density at 15°C	0.878-0.888 g/cm ³
Kinematic Viscosity at 40°C	450-550 cSt
Kinematic Viscosity at 100°C	29-35 cSt
Viscosity Index	110 min
Flash Point (COC)	290°C min
Pour Point	-3°C max
Aniline Point	125-138°C
Carbon Type Analysis - CA%	< 0.5%
Carbon Type Analysis - CN%	15-23%
Carbon Type Analysis - CP%	78-84%
Sulphur Content	0.01% max
Color ASTM	L 2.0 max
FDA 21 CFR 178.3620	Compliant

Applications

Premium EPDM compounds, automotive door seals, window profiles, white/colored rubber

Performance Standards

IS 13631

Handling & Storage

- Store in a cool, dry place away from direct sunlight
- Keep container tightly closed when not in use
- Shelf life: 36 months from date of manufacture
- Do not mix with other lubricants