

# JoshRub

351 Aromatic Rubber Process Oil

## Product Description

JoshRub is a premium Light Diesel Oil Distillation Residue / Recycled Oil Residue Aromatic Rubber Process Oil designed for Heavy duty tire compounds, reclaimed rubber, low cost rubber goods, hard rubber products. Meets IS 13631 Heavy Grade specifications and delivers exceptional performance in demanding conditions.

## Technical Specifications

|                              |                                    |
|------------------------------|------------------------------------|
| Appearance                   | Black viscous liquid               |
| Density at 15°C              | 1.010-1.040 g/cm³                  |
| Kinematic Viscosity at 100°C | 35-50 cSt                          |
| Kinematic Viscosity at 40°C  | 550-750 cSt                        |
| Flash Point (COC)            | 250°C min                          |
| Pour Point                   | 40°C max                           |
| Aniline Point                | 28-38°C                            |
| Carbon Type Analysis - CA%   | 50-65%                             |
| Carbon Type Analysis - CN%   | 20-30%                             |
| Carbon Type Analysis - CP%   | 10-20%                             |
| Sulphur Content              | 5-8%                               |
| Hardness Enhancement         | High - harder than standard grades |
| Ash Content                  | 0.1% max                           |
| Cost Effectiveness           | Economical grade                   |

## Applications

Heavy duty tire compounds, reclaimed rubber, low cost rubber goods, hard rubber products

## Performance Standards

IS 13631 Heavy Grade

## Handling & Storage

- Store in a cool, dry place away from direct sunlight
- Keep container tightly closed when not in use
- Shelf life: 36 months from date of manufacture
- Do not mix with other lubricants